

Anti-Vibe®, Stud Style, Inch Acme

ACME THREADED LEVELING MOUNTS

INTRODUCING: ACME THREADED LEVELING MOUNTS

AVAILABLE IN THESE POPULAR BRANDS:
PolyMount™, Low Profile and Level-IT®

Light Duty

S&W P/N Steel	S&W P/N Stainless	Thread (A)	Base Dia. (B)	Thread Length (C)	Total Height (D)	Hex Size (E)	Max Load (lbs)
BSW-1L-ACME1	SS-BSW-1L-ACME1	3/8-12	1 1/4	2	1 1/2	5/8	300
BSW-2L-ACME1	SS-BSW-2L-ACME1	1/2-10	1 7/8	2	1 3/4	3/4	750
BSW-3L-ACME1	SS-BSW-3L-ACME1	5/8-8	2 1/2	2	1 7/8	7/8	1350
BSW-4L-ACME1	SS-BSW-4L-ACME1	3/4-6	3	2	4 1/8	1 1/16	1875
BSW-5L-ACME1	SS-BSW-5L-ACME1	1-5	4	3 1/2	6	1 3/8	3375
BSW-6L-ACME1	SS-BSW-6L-ACME1	1 1/4-5	6	4	6 7/8	1 7/8	7500

Medium Duty

S&W P/N Steel	S&W P/N Stainless	Thread (A)	Base Dia. (B)	Thread Length (C)	Total Height (D)	Hex Size (E)	Max Load (lbs)
BSW-1M-ACME1	SS-BSW-1M-ACME1	3/8-12	1 1/4	2	1 1/2	5/8	600
BSW-2M-ACME1	SS-BSW-2M-ACME1	1/2-10	1 7/8	2	1 3/4	3/4	1500
BSW-3M-ACME1	SS-BSW-3M-ACME1	5/8-8	2 1/2	2	3 7/8	7/8	2700
BSW-4M-ACME1	SS-BSW-4M-ACME1	3/4-6	3	2	4 1/8	1 1/16	3750
BSW-5M-ACME1	SS-BSW-5M-ACME1	1-5	4	3 1/2	6	1 3/8	6750
BSW-6M-ACME1	SS-BSW-6M-ACME1	1 1/4-5	6	4	6 7/8	1 7/8	15000

Heavy Duty

S&W P/N Steel	S&W P/N Stainless	Thread (A)	Base Dia. (B)	Thread Length (C)	Total Height (D)	Hex Size (E)	Max Load (lbs)
BSW-1H-ACME1	SS-BSW-1H-ACME1	3/8-12	1 1/4	2	3 1/2	5/8	1490
BSW-2H-ACME1	SS-BSW-2H-ACME1	1/2-10	1 7/8	2	3 3/4	3/4	3600
BSW-3H-ACME1	SS-BSW-3H-ACME1	5/8-8	2 1/2	2	3 7/8	7/8	6600
BSW-4H-ACME1	SS-BSW-4H-ACME1	3/4-6	3	2	4 1/8	1 1/16	9750
BSW-5H-ACME1	SS-BSW-5H-ACME1	1-5	4	3 1/2	6	1 3/8	17500
BSW-6H-ACME1	SS-BSW-6H-ACME1	1 1/4-5	6	4	6 7/8	1 7/8	40000

Low Profile, Standard Base, Inch Acme

S&W P/N Steel	S&W P/N Stainless	Steel Thread (A)	Base Dia. (B)	Thread Length (C)	Overall Height (D)	Hex Size (E)	Max Load (lbs)
LP1-A4-ACME1	SLP1-A4-ACME1	3/8-12	2	4	5	3/4	3000
LP1-A6-ACME1	SLP1-A6-ACME1	3/8-12	2	6	7	3/4	3000
LP1-B4-ACME1	SLP1-B4-ACME1	1/2-10	2	4	5	3/4	5250
LP1-B6-ACME1	SLP1-B6-ACME1	1/2-10	2	6	7	3/4	5250
LP1-C4-ACME1	SLP1-C4-ACME1	5/8-8	2	4	5	7/8	7500
LP1-C6-ACME1	SLP1-C6-ACME1	5/8-8	2	6	7	7/8	7500
LP2-A4-ACME1	SLP2-A4-ACME1	3/8-12	2 1/2	4	5	3/4	3000
LP2-A6-ACME1	SLP2-A6-ACME1	3/8-12	2 1/2	6	7	3/4	3000
LP2-B4-ACME1	SLP2-B4-ACME1	1/2-10	2 1/2	4	5	3/4	5250
LP2-B6-ACME1	SLP2-B6-ACME1	1/2-10	2 1/2	6	7	3/4	5250
LP2-C4-ACME1	SLP2-C4-ACME1	5/8-8	2 1/2	4	5	7/8	7500
LP2-C6-ACME1	SLP2-C6-ACME1	5/8-8	2 1/2	6	7	7/8	7500
LP3-B6-ACME1	SLP3-B6-ACME1	1/2-10	3	6	7	3/4	5250
LP3-C4-ACME1	SLP3-C4-ACME1	5/8-8	3	4	5	7/8	7500
LP3-C6-ACME1	SLP3-C6-ACME1	5/8-8	3	6	7	7/8	7500
LP3-D4-ACME1	SLP3-D4-ACME1	3/4-6	3	4	5	1 1/16	9000
LP3-D6-ACME1	SLP3-D6-ACME1	3/4-6	3	6	7	1 1/16	9000
LP4-B4-ACME1	SLP4-B4-ACME1	1/2-10	4	4	5	3/4	5250
LP4-B6-ACME1	SLP4-B6-ACME1	1/2-10	4	6	7	3/4	5250
LP4-C4-ACME1	SLP4-C4-ACME1	5/8-8	4	4	5	7/8	7500
LP4-C6-ACME1	SLP4-C6-ACME1	5/8-8	4	6	7	7/8	7500
LP4-D4-ACME1	SLP4-D4-ACME1	3/4-6	4	4	5	1 1/16	9000
LP4-D6-ACME1	SLP4-D6-ACME1	3/4-6	4	6	7	1 1/16	9000
LP4-E4-ACME1	SLP4-E4-ACME1	1-5	4	4	5	1 3/8	11250
LP4-E6-ACME1	SLP4-E6-ACME1	1-5	4	6	7	1 3/8	11250

Once again S&W Manufacturing is leading the market because of your requests. S&W Manufacturing is pleased to offer Acme threads as an option on all future leveling mount orders. The Acme thread offers fewer threads per inch, allowing for faster adjustment and nearly double the weight capacities than standard UNC threads.

S&W's full line leveling mount products can now be specified with either standard threads, or the Acme thread, depending on our customers' needs. In addition, all S&W threaded tube ends can now be provided with the Acme thread to accommodate our leveling line.



216 S. Evergreen St. Bensenville, IL 60106
PH: 630-595-5044 x233/FX: 630-595-5275

When you level with someone...
level with us!TM

888-LEVEL-IT (538-3548) swmanufacturing.com



888-LEVEL-IT (538-3548) swmanufacturing.com

Level-It®, Inch Acme with stud



S&W P/N Steel	S&W P/N Stainless	Thread (A)	Base Dia. (B)	Thread Length (C)	Total Height (D)	Hex Size (E)	Max Load (lbs)
BSW-0-ACME1	SSW-0-ACME1	1/4-16	1	1 1/4	115/16	1/2	1500
BSW-0A-ACME1	SSW-0A-ACME1	1/4-16	1	2 1/2	3 3/16	1/2	1500
BSW-100-ACME1	SSW-100-ACME1	5/16-14	1 1/4	2	2 7/8	5/8	3750
BSW-100A-ACME1	SSW-100A-ACME1	5/16-14	1 1/4	4	4 7/8	5/8	3750
BSW-1-ACME1	SSW-1-ACME1	3/8-12	1 1/4	2	2 7/8	5/8	5625
BSW-1A-ACME1	SSW-1A-ACME1	3/8-12	1 1/4	4	4 7/8	5/8	5625
BSW-2-ACME1	SSW-2-ACME1	1/2-10	1 7/8	2	3 1/8	3/4	7500
BSW-2A-ACME1	SSW-2A-ACME1	1/2-10	1 7/8	4	5 1/8	3/4	7500
BSW-3-ACME1	SSW-3-ACME1	5/8-8	2 1/2	2	3 1/4	7/8	9000
BSW-3A-ACME1	SSW-3A-ACME1	5/8-8	2 1/2	4	5 1/4	7/8	9000
BSW-4-ACME1	SSW-4-ACME1	3/4-6	3	2	3 1/2	1 1/16	11100
BSW-4A-ACME1	SSW-4A-ACME1	3/4-6	3	4	5 1/2	1 1/16	11100
BSW-5-ACME1	SSW-5-ACME1	1-5	4	3 1/2	5 3/8	1 3/8	30000
BSW-5EL-ACME1	SSW-5EL-ACME1	1-5	4	4 1/4	6 1/8	1 3/8	30000
BSW-5A-ACME1	SSW-5A-ACME1	1-5	4	6	7 7/8	1 3/8	30000
BSW-5G-ACME1	SSW-5G-ACME1	1-5	4	8	9 7/8	1 3/8	30000
BSW-6-ACME1	SSW-6-ACME1	1 1/4-5	6	4	6 3/4	1 7/8	60000
BSW-6EL-ACME1	SSW-6EL-ACME1	1 1/4-5	6	6	8 3/4	1 7/8	60000

PolyMounts™, Stud Style, Inch Acme



S&W P/N Steel	S&W P/N Stainless	Thread (A)	Base Dia. (B)	Thread Length (C)	Total Height (D)	Hex Size (E)	Max Load (lbs)
BNYLA13-ACME1	BSNYLA13-ACME1	3/8-12	1.58	2 5/8	3 11/16	5/8	3750
BNYLA24-ACME1	BSNYLA24-ACME1	3/8-12	2	4	5 1/8	3/4	5000
BNYLA26-ACME1	BSNYLA26-ACME1	3/8-12	2	6	7 1/8	3/4	5000
BNYLB24-ACME1	BSNYLB24-ACME1	1/2-10	2	4	5 1/8	3/4	5000
BNYLB26-ACME1	BSNYLB26-ACME1	1/2-10	2	6	7 1/8	3/4	5000
BNYLC24-ACME1	BSNYLC24-ACME1	5/8-8	2	4	5 1/8	7/8	5000
BNYLC26-ACME1	BSNYLC26-ACME1	5/8-8	2	6	7 1/8	7/8	5000
BNYLA34-ACME1	BSNYLA34-ACME1	3/8-12	3	4	5 1/8	3/4	6000
BNYLA36-ACME1	BSNYLA36-ACME1	3/8-12	3	6	7 1/8	3/4	6000
BNYLB34-ACME1	BSNYLB34-ACME1	1/2-10	3	4	5 1/8	3/4	6000
BNYLB36-ACME1	BSNYLB36-ACME1	1/2-10	3	6	7 1/8	3/4	6000
BNYLC34-ACME1	BSNYLC34-ACME1	5/8-8	3	4	5 1/8	7/8	6000
BNYLC36-ACME1	BSNYLC36-ACME1	5/8-8	3	6	7 1/8	7/8	6000
BNYLD34-ACME1	BSNYLD34-ACME1	3/4-6	3	4	5 1/8	1 1/16	6000
BNYLD36-ACME1	BSNYLD36-ACME1	3/4-6	3	6	7 1/8	1 1/16	6000
BNYLC44-ACME1	BSNYLC44-ACME1	5/8-8	4	4	5 5/16	7/8	7500
BNYLC46-ACME1	BSNYLC46-ACME1	5/8-8	4	6	7 5/16	7/8	7500
BNYLD44-ACME1	BSNYLD44-ACME1	3/4-6	4	4	5 5/16	1 1/16	7500
BNYLD46-ACME1	BSNYLD46-ACME1	3/4-6	4	6	7 5/16	1 1/16	7500
BNYLE44-ACME1	BSNYLE44-ACME1	1-5	4	4	5 5/16	1 3/8	7500
BNYLE46-ACME1	BSNYLE46-ACME1	1-5	4	6	7 5/16	1 3/8	7500
BNYLE48-ACME1	BSNYLE48-ACME1	1-5	4	8	9 5/16	1 3/8	7500

PolyMounts™, Stud Style, Inch Acme

S&W P/N Steel	S&W P/N Stainless	Thread (A)	Base Dia. (B)	Thread Length (C)	Total Height (D)	Hex Size (E)	Max Load (lbs)
BNYLC54-ACME1	BSNYLC54-ACME1	5/8-8	5	4	6 1/4	1 1/16	12000
BNYLC56-ACME1	BSNYLC56-ACME1	5/8-8	5	6	8 1/4	1 1/16	12000
BNYLC58-ACME1	BSNYLC58-ACME1	5/8-8	5	8	10 1/4	1 1/16	12000
BNYLC510-ACME1	BSNYLC510-ACME1	5/8-8	5	10	12 1/4	1 1/16	12000
BNYLD54-ACME1	BSNYLD54-ACME1	3/4-6	5	4	6 1/4	1 1/16	12000
BNYLD56-ACME1	BSNYLD56-ACME1	3/4-6	5	6	8 1/4	1 1/16	12000
BNYLD58-ACME1	BSNYLD58-ACME1	3/4-6	5	8	10 1/4	1 1/16	12000
BNYLD510-ACME1	BSNYLD510-ACME1	3/4-6	5	10	12 1/4	1 1/16	12000
BNYLE54-ACME1	BSNYLE54-ACME1	1-5	5	4	6 1/4	1 3/8	12000
BNYLE56-ACME1	BSNYLE56-ACME1	1-5	5	6	8 1/4	1 3/8	12000
BNYLE58-ACME1	BSNYLE58-ACME1	1-5	5	8	10 1/4	1 3/8	12000
BNYLE510-ACME1	BSNYLE510-ACME1	1-5	5	10	12 1/4	1 3/8	12000
BNYLF54-ACME1	BSNYLF54-ACME1	1 1/8-5	5	4	6 1/4	1 3/8	12000
BNYLF56-ACME1	BSNYLF56-ACME1	1 1/8-5	5	6	8 1/4	1 3/8	12000
BNYLF58-ACME1	BSNYLF58-ACME1	1 1/8-5	5	8	10 1/4	1 3/8	12000
BNYLF510-ACME1	BSNYLF510-ACME1	1 1/8-5	5	10	12 1/4	1 3/8	12000
BNYLG54-ACME1	BSNYLG54-ACME1	1 1/4-5	5	4	6 1/4	1 7/8	12000
BNYLG56-ACME1	BSNYLG56-ACME1	1 1/4-5	5	6	8 1/4	1 7/8	12000
BNYLG58-ACME1	BSNYLG58-ACME1	1 1/4-5	5	8	10 1/4	1 7/8	12000
BNYLG510-ACME1	BSNYLG510-ACME1	1 1/4-5	5	10	12 1/4	1 7/8	12000

Teardrop PolyMounts™, Inch Acme



S&W P/N Steel	S&W P/N Stainless	Thread (A)	Base Dia. (B)	Base Width	Thread Length (C)	Total Height (D)	Hex Size (E)	Max Load (lbs)
TNYLB44-ACME1	TSNYLB44-ACME1	1/2-10	4	5 7/16	4	5 5/16	3/4	6000
TNYLB46-ACME1	TSNYLB46-ACME1	1/2-10	4	5 7/16	6	7 5/16	3/4	6000
TNYLB48-ACME1	TSNYLB48-ACME1	1/2-10	4	5 7/16	8	9 5/16	3/4	6000
TNYLC44-ACME1	TSNYLC44-ACME1	5/8-8	4	5 7/16	4	5 5/16	7/8	7000
TNYLC46-ACME1	TSNYLC46-ACME1	5/8-8	4	5 7/16	6	7 5/16	7/8	7000
TNYLC48-ACME1	TSNYLC48-ACME1	5/8-8	4	5 7/16	8	9 5/16	7/8	7000
TNYLD44-ACME1	TSNYLD44-ACME1	3/4-6	4	5 7/16	4	5 5/16	1 1/16	7500
TNYLD46-ACME1	TSNYLD46-ACME1	3/4-6	4	5 7/16	6	7 5/16	1 1/16	7500
TNYLD48-ACME1	TSNYLD48-ACME1	3/4-6	4	5 7/16	8	9 5/16	1 1/16	7500
TNYLE44-ACME1	TSNYLE44-ACME1	1-5	4	5 7/16	4	5 5/16	1 3/8	7500
TNYLE46-ACME1	TSNYLE46-ACME1	1-5	4	5 7/16	6	7 5/16	1 3/8	7500
TNYLE48-ACME1	TSNYLE48-ACME1	1-5	4	5 7/16	8	9 5/16	1 3/8	7500

Threaded Tube Ends for Square Tubes, Inch Acme

S&W P/N	Thread (A)	OD (B)	Tube Gauge/Shape	Tube Size OD	Wall	Static Load (lbs)
TE1-2A-ACME1	3/8-12	1.5 sq.	16 ga. square	1.5 sq.	.065	1500
TE1-2B-ACME1	1/2-10	1.5 sq.	16 ga. square	1.5 sq.	.065	1500
TE1-2C-ACME1	5/8-8	1.5 sq.	16 ga. square	1.5 sq.	.065	1500
TE1-2D-ACME1	3/4-6	1.5 sq.	16 ga. square	1.5 sq.	.065	1500
TE1-3A-ACME1	3/8-12	1.5 sq.	11 ga. square	1.5 sq.	.120	1500
TE1-3B-ACME1	1/2-10	1.5 sq.	11 ga. square	1.5 sq.	.120	1500
TE1-3C-ACME1	5/8-8	1.5 sq.	11 ga. square	1.5 sq.	.120	1500
TE1-3D-ACME1	3/4-6	1.5 sq.	11 ga. square	1.5 sq.	.120	1500
TE2-1A-ACME1	3/8-12	2.0 sq.	16 ga. square	2.0 sq.	.065	2000
TE2-1B-ACME1	1/2-10	2.0 sq.	16 ga. square	2.0 sq.	.065	2000
TE2-1C-ACME1	5/8-8	2.0 sq.	16 ga. square	2.0 sq.	.065	2000
TE2-1D-ACME1	3/4-6	2.0 sq.	16 ga. square	2.0 sq.	.065	2000
TE2-3A-ACME1	3/8-12	2.0 sq.	11-12 ga. square	2.0 sq.	.109/120	2000
TE2-3B-ACME1	1/2-10	2.0 sq.	11-12 ga. square	2.0 sq.	.109/120	2000
TE2-3C-ACME1	5/8-8	2.0 sq.	11-12 ga. square	2.0 sq.	.109/120	2000
TE2-3D-ACME1	3/4-6	2.0 sq.	11-12 ga. square	2.0 sq.	.109/120	2000

Threaded Tube Ends for Round Tubes, Inch Acme

S&W P/N	Thread (A)	OD (B)	Tube Gauge/Shape	Tube Size OD	Wall	Static Load (lbs)
TE1-1A-ACME1	3/8-12	1.5 dia.	16 ga. round	1.5 dia.	.065	1500
TE1-1B-ACME1	1/2-10	1.5 dia.	16 ga. round	1.5 dia.	.065	1500
TE1-1C-ACME1	5/8-8	1.5 dia.	16 ga. round	1.5 dia.	.065	1500
TE1-1D-ACME1	3/4-6	1.5 dia.	16 ga. round	1.5 dia.	.065	1500
TE1-4A-ACME1	3/8-12	2.0 dia.	1.5" Sch 5 pipe	1.9 dia.	.065	1500
TE1-4B-ACME1	1/2-10	2.0 dia.	1.5" Sch 5 pipe	1.9 dia.	.065	1500
TE1-4C-ACME1	5/8-8	2.0 dia.	1.5" Sch 5 pipe	1.9 dia.	.065	1500
TE1-4D-ACME1	3/4-6	2.0 dia.	1.5" Sch 5 pipe	1.9 dia.	.065	1500
TE1-10A-ACME1	3/8-12	2.0 dia.	20" Sch 10 pipe	1.9 dia.	.109	2000
TE1-10B-ACME1	1/2-10	2.0 dia.	20" Sch 10 pipe	1.9 dia.	.109	2000
TE1-10C-ACME1	5/8-8	2.0 dia.	20" Sch 10 pipe	1.9 dia.	.109	2000
TE1-10D-ACME1	3/4-6	2.0 dia.	20" Sch 10 pipe	1.9 dia.	.109	2000
TE2-2A-ACME1	3/8-12	2.0 dia.	16 ga. round	2.0 dia.	.065	2000
TE2-2B-ACME1	1/2-10	2.0 dia.	16 ga. round	2.0 dia.	.065	2000
TE2-2C-ACME1	5/8-8	2.0 dia.	16 ga. round	2.0 dia.	.065	2000
TE2-2D-ACME1	3/4-6	2.0 dia.	16 ga. round	2.0 dia.	.065	2000

When you level with someone...
level with us!™